

TECHNICAL HEALTH AND DATA SHEET

A FAST DRYING ANTI-CORROSIVE INDUSTRIAL FINISH, GIVING A GOOD DURABLE PROTECTIVE COATING TO METAL SURFACES.

PRODUCT:- CHASSIS BLACK

REFERENCE:- G/770/2

COLOUR:- BLACK

FINISH:- SEMI-GLOSS

TYPE:- MODIFIED ALKYD

TYPICAL SG:- 1.11 @20C.

TYPICAL VISCOSITY:- 2 –2.5 POISE (C&P)AT 25C

TYPICAL TOTAL SOLIDS:- 52.0% BY WEIGHT

TYPICAL FLASH POINT:- 25°C

RECOMMENDED THINNERS:- V/607/16

APPLICATION:- SPRAY, SMALL AREAS MAY
BE BRUSHED

*COVERAGE GUIDE:- 10 SQ. METRES/LITRE

*DRYING TIME:- SURFACE DRY - 30 MINUTES
THROUGH DRY - 4 HOURS

USES:- AS A QUICK DRYING FINISH,
IDEAL FOR STRUCTURAL STEEL
AND METAL FABRICATIONS.

HEALTH & SAFETY:- SEE SDS 10889

RECOMMENDED PRIMER:- USE AS A PRIMER AND A FINISH

*BY SPRAY TO A DRY FILM THICKNESS OF 40 MICRONS AT 20°C.

Teamac® Paints

MANUFACTURERS OF DECORATIVE, MARINE AND INDUSTRIAL
COATINGS

Teal & Mackrill Limited,
Lockwood Street, HULL. HU2 OHN
Telephone: 01482-320194 Fax: 01482-219266