



SAFETY DATA SHEET
135/W222 - PROFLOOR BASE + COLOURANTS (ALL TINTS + GREY)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name 135/W222 - PROFLOOR BASE + COLOURANTS (ALL TINTS + GREY)
Product No. 135/W222/bases + colourant (All tints + 138)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses BASE FOR TWO COMPONENT FLOOR COATING

1.3. Details of the supplier of the safety data sheet

Supplier COO-VAR
Lockwood Street
Hull
HU2 0HN
+44 (0) 1482 328053(T)
+44 (0) 1482 219266(F)
info@coo-var.co.uk
Contact Person Technical Department - 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri as above

1.4. Emergency telephone number

+44 (0) 1482 328053 (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Hazards Not classified.
Human health Skin Irrit. 2 - H315; Eye Irrit. 2 - H319; Skin Sens. 1 - H317
Environment Aquatic Chronic 2 - H411

Classification (1999/45/EEC) Xi; R36/38. R43. N; R51/53.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Human health

The product contains a small amount of sensitising substance which may provoke an allergic reaction among sensitive individuals in contact with skin.

Physical and Chemical Hazards

When handled correctly, undamaged units represent no danger.

2.2. Label elements

Contains REACTION PRODUCT : BISPHENOL A-(EPICHLOROHYDRIN):EPOXY RESIN (NUMBER AVERAGE MW<=700)
FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH
1-CHLORO-2,3-EPOXYPROPANE AND PHENOL
OXIRANE, MONO [(C12-14- ALKYL OXY)METHYL] DERIVS

Label In Accordance With (EC) No. 1272/2008

135/W222 - PROFLOOR BASE + COLOURANTS (ALL TINTS + GREY)



Signal Word	Warning	
Hazard Statements	H315	Causes skin irritation.
	H317	May cause an allergic skin reaction.
	H319	Causes serious eye irritation.
	H411	Toxic to aquatic life with long lasting effects.
Precautionary Statements	P102	Keep out of reach of children.
	P101	If medical advice is needed, have product container or label at hand.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/protective clothing/eye protection/face protection.
	P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P313	Get medical advice/attention.
	P501A	Dispose of contents/container to special waste collection point
Supplementary Precautionary Statements	P272	Contaminated work clothing should not be allowed out of the workplace.
	P261	Avoid breathing vapour/spray.
	P264	Wash contaminated skin thoroughly after handling.
	P321	Specific treatment (see medical advice on this label).
	P302+352	IF ON SKIN: Wash with plenty of soap and water.
	P332+313	If skin irritation occurs: Get medical advice/attention.
	P333+313	If skin irritation or rash occurs: Get medical advice/attention.
	P337	If eye irritation persists:
	P362	Take off contaminated clothing and wash before reuse.
	P363	Wash contaminated clothing before reuse.
	P391	Collect spillage.
Supplemental label information	EUH205	Contains epoxy constituents. May produce an allergic reaction.

2.3. Other hazards

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

REACTION PRODUCT : BISPHENOL A-(EPICHLOROHYDRIN):EPOXY RESIN (NUMBER AVERAGE MW<=700)		30-60%
CAS-No.: 25068-38-6	EC No.: 500-033-5	
Classification (EC 1272/2008)	Classification (67/548/EEC)	
Skin Irrit. 2 - H315	R43	
Eye Irrit. 2 - H319	Xi;R36/38	
Skin Sens. 1 - H317	N;R51/53	
Aquatic Chronic 2 - H411		

135/W222 - PROFLOOR BASE + COLOURANTS (ALL TINTS + GREY)

Barium Sulphate		10-30%
CAS-No.: 7727-43-7	EC No.: 231-784-4	Registration Number: 01-2119491274-35-0001
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.	
FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL		10-30%
CAS-No.: 9003-36-5	EC No.: 500-006-8	
Classification (EC 1272/2008) Skin Irrit. 2 - H315 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411	Classification (67/548/EEC) Xi;R38. N;R51/53. R43.	
Diatomaceous Earth		10-30%
CAS-No.: 61790-53-2	EC No.: 310-127-6	
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.	
Calcium Magnesium Silicate		5-10%
CAS-No.: 14807-96-6	EC No.: 238-877-9	
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.	
OXIRANE, MONO [(C12-14- ALKYLOXY)METHYL] DERIVS		5-10%
CAS-No.: 68609-97-2	EC No.:	
Classification (EC 1272/2008) Skin Irrit. 2 - H315 Skin Sens. 1 - H317	Classification (67/548/EEC) R43 Xi;R38	
dodecylphenol, ethoxylated		<1%
CAS-No.: 9014-92-0	EC No.:	
Classification (EC 1272/2008) Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Aquatic Chronic 2 - H411	Classification (67/548/EEC) Xi;R36/38. N;R51/53.	

135/W222 - PROFLOOR BASE + COLOURANTS (ALL TINTS + GREY)

2-METHYLPENTANE-2,4-DIOL		<1%
CAS-No.: 107-41-5	EC No.: 203-489-0	
Classification (EC 1272/2008) Skin Irrit. 2 - H315 Eye Irrit. 2 - H319	Classification (67/548/EEC) Xi;R36/38	
Alkylphenoethersulfat-sodium salt		<1%
CAS-No.: 109909-39-9	EC No.:	
Classification (EC 1272/2008) Eye Dam. 1 - H318 Aquatic Chronic 2 - H411	Classification (67/548/EEC) Xi;R41. N;R51/53.	
phosphoric acid ester, neutralised		<1%
CAS-No.: 68954-84-7	EC No.:	
Classification (EC 1272/2008) Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Aquatic Chronic 2 - H411	Classification (67/548/EEC) Xi;R38,R41. N;R51/53.	
isotridecylalcohol,ethoxylated,phosphated,compd. with N,N-dimethylcyclohexanamine		<1%
CAS-No.: 164383-18-0	EC No.:	
Classification (EC 1272/2008) Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Aquatic Chronic 2 - H411	Classification (67/548/EEC) Xi;R36/38. N;R51/53.	
nonylphenol, branched, ethoxylated, phosphate		<1%
CAS-No.:	EC No.:	
Classification (EC 1272/2008) Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Aquatic Chronic 2 - H411	Classification (67/548/EEC) Xi;R38,R41. N;R51/53.	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General information

General first aid, rest, warmth and fresh air. Do not give victim anything to drink if they are unconscious.

Inhalation

Remove victim immediately from source of exposure. Provide rest, warmth and fresh air. Get medical attention if any discomfort continues. Place unconscious person on the side in the recovery position and ensure breathing can take place.

135/W222 - PROFLOOR BASE + COLOURANTS (ALL TINTS + GREY)

Ingestion

Immediately give a couple of glasses of water or milk, provided the victim is fully conscious. Do not induce vomiting. Get medical attention if any discomfort continues.

Skin contact

Remove affected person from source of contamination. Wash off promptly and flush contaminated skin with water. Promptly remove clothing if soaked through and flush skin with water. Get medical attention if irritation persists after washing.

Eye contact

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Get medical attention immediately. Continue to rinse.

4.2. Most important symptoms and effects, both acute and delayed

General information

If adverse symptoms develop as described the casualty should be transferred to hospital as soon as possible.

4.3. Indication of any immediate medical attention and special treatment needed

No recommendation given, but first aid may still be required in case of accidental exposure, inhalation or ingestion of this chemical. If in doubt, GET MEDICAL ATTENTION PROMPTLY!

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media

Non flammable at room temperature, but will burn. Use fire-extinguishing media appropriate for surrounding materials. Fire can be extinguished using: Water spray, fog or mist. Foam, carbon dioxide or dry powder.

5.2. Special hazards arising from the substance or mixture

Specific hazards

When heated and in case of fire, harmful vapours/gases may be formed.

5.3. Advice for firefighters

Special Fire Fighting Procedures

Avoid breathing fire vapours. Containers close to fire should be removed or cooled with water.

Protective equipment for fire-fighters

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation. Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Avoid discharge into drains, water courses or onto the ground. Contain spillages with sand, earth or any suitable adsorbent material.

Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Should be prevented from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

6.4. Reference to other sections

For personal protection, see section 8.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

135/W222 - PROFLOOR BASE + COLOURANTS (ALL TINTS + GREY)

Avoid inhalation of vapours. Avoid spilling, skin and eye contact. Do not eat, drink or smoke when using the product. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. The Manual Handling Operations Regulations may apply to the handling of containers of this product. For products sold by weight refer to the guide net weight indicated on the container. Allowance will have to be made for the immediate packaging to give an approximate gross weight.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed original container in a dry, cool and well-ventilated place. Store in closed original container at temperatures between 5°C and 25°C. Protect from freezing and direct sunlight. Keep upright.

7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

Usage Description

Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in a suitably labelled container.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
2-METHYLPENTANE-2,4-DIOL	WEL	25 ppm	123 mg/m3	25 ppm	123 mg/m3	
Barium Sulphate	WEL		10 mg/m3			
Calcium Magnesium Silicate	WEL		1 mg/m3			
Diatomaceous Earth	WEL		1.2 mg/m3			

WEL = Workplace Exposure Limit.

Ingredient Comments

WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment



Process conditions

Use engineering controls to reduce air contamination to permissible exposure level.

Engineering measures

Provide adequate ventilation. Observe Occupational Exposure Limits and minimise the risk of inhalation of vapours.

Respiratory equipment

No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

Hand protection

Use suitable protective gloves if risk of skin contact. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material. Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin.

Eye protection

Wear approved chemical safety goggles where eye exposure is reasonably probable.

Other Protection

Wear appropriate clothing to prevent reasonably probable skin contact.

Hygiene measures

No specific hygiene procedures noted, but good personal hygiene practices are always advisable, especially when working with chemicals.

Personal protection

Unprotected persons should be kept away from treated areas.

135/W222 - PROFLOOR BASE + COLOURANTS (ALL TINTS + GREY)**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES****9.1. Information on basic physical and chemical properties**

Appearance	Coloured liquid.
Odour	Sweetish.
Solubility	Immiscible with water
Initial boiling point and boiling range (°C)	>150 760 mm Hg
Relative density	1.12 @ 25C
Vapour pressure	<0.1 mbar @ 20 C
Viscosity	0.90 Pas @ 25 C
Auto Ignition Temperature (°C)	>200

9.2. Other information

Volatile By Vol. (%)	0 - 4%
Volatile Organic Compound (VOC)	0 g/litre

SECTION 10: STABILITY AND REACTIVITY**10.1. Reactivity**

No specific reactivity hazards associated with this product.

10.2. Chemical stability

Stable under normal temperature conditions and recommended use.

10.3. Possibility of hazardous reactions

Hazardous Polymerisation
Will not occur

10.4. Conditions to avoid

Not known.

10.5. Incompatible materials

Materials To Avoid
Strong acids. Bases, alkalis (inorganic). Amines. Mercaptans (thiols).

10.6. Hazardous decomposition products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: TOXICOLOGICAL INFORMATION**11.1. Information on toxicological effects**

Toxicological information
No data recorded.

General information
No specific health warnings noted.

Inhalation
May cause irritation to the respiratory system.

Ingestion
Harmful if swallowed. Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract.

135/W222 - PROFLOOR BASE + COLOURANTS (ALL TINTS + GREY)

Skin contact

Irritating to skin. May cause sensitisation by skin contact.

Eye contact

Irritating to eyes.

Health Warnings

May cause sensitisation by skin contact. Delayed appearance of the complaints and development of hypersensitivity (difficulty breathing, coughing, asthma) are possible.

Route of entry

Inhalation. Skin absorption. Ingestion. Skin and/or eye contact.

Medical Considerations

Skin disorders and allergies.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

There are no data on the ecotoxicity of this product.

12.1. Toxicity

Acute Fish Toxicity

Toxicity to bacteria, algae and higher marine organisms not tested. COD: Not determined

12.2. Persistence and degradability

Degradability

No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential

No data available on bioaccumulation.

12.4. Mobility in soil

Mobility:

The product is non-volatile.

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

Not determined.

SECTION 13: DISPOSAL CONSIDERATIONS

General information

Do not allow to enter drains, sewers or watercourses. Waste to be treated as controlled waste. Disposal to licensed waste disposal site in accordance with local Waste Disposal Authority. When handling waste, consideration should be made to the safety precautions applying to handling of the product. DO NOT reuse containers containing residual product without commercial cleaning

13.1. Waste treatment methods

Waste Class

When this material, in its liquid state, as supplied, becomes a waste, it is categorised as a hazardous waste, with code 08 01 11* (EPOXY BASED LIQUID WASTE). Part-used containers, not drained and/or rigorously scraped out and containing residues of the supplied material, are categorised as hazardous waste, with code 08 01 11* (EPOXY BASED LIQUID WASTE). Ideally this component should be mixed with the appropriate hardener and allowed to react fully to produce a solid waste. Neutralised empty packages, are categorised as non-hazardous waste, with code 15 01 02(plastic packaging) or 15 01 04 (metal packaging)

SECTION 14: TRANSPORT INFORMATION

General

This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG.

135/W222 - PROFLOOR BASE + COLOURANTS (ALL TINTS + GREY)**14.1. UN number**

UN No. (ADR/RID/ADN) 3082

UN No. (IMDG) 3082

14.2. UN proper shipping name

Proper Shipping Name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

14.3. Transport hazard class(es)

ADR/RID/ADN Class 9

ADR/RID/ADN Class Class 9: Environmentally hazardous substance, liquid, N.O.S. contains: epoxy constituents

ADR/RID/ADN Subsidiary Risk HAZARD ID 90

IMDG Class 9

ICAO Class/Division 9

Transport Labels

**14.4. Packing group**

ADR/RID/ADN Packing group III

IMDG Packing group III

ICAO Packing group III

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant

**14.6. Special precautions for user**

EMS F-A S-F

Tunnel Restriction Code (E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

SECTION 15: REGULATORY INFORMATION**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Uk Regulatory References

The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments.

Statutory Instruments

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716). Control of Substances Hazardous to Health.

135/W222 - PROFLOOR BASE + COLOURANTS (ALL TINTS + GREY)

Approved Code Of Practice

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply. Dangerous Substances and Explosive Atmospheres Regulations 2002 [L138]

Guidance Notes

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

EU Legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

National Regulations

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. No. 1689.

15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

SECTION 16: OTHER INFORMATION

Revision Comments

Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 453/2010 Update for CLP labelling.

Issued By	Technical Dept. (P.E.)
Revision Date	18/05/2015
Revision	5
Supersedes date	25/10/2012
SDS No.	10398
Safety Data Sheet Status	Approved.
Date	Date printed _____
Signature	Initials _____

Risk Phrases In Full

R36/38	Irritating to eyes and skin.
R38	Irritating to skin.
R43	May cause sensitisation by skin contact.
NC	Not classified.
R41	Risk of serious damage to eyes.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Hazard Statements In Full

H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.