



SAFETY DATA SHEET

413/G750 - RAPIDRY GLOSS - BLACK

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name 413/G750 - RAPIDRY GLOSS - BLACK

Product number 413/G750/2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Paint.

1.3. Details of the supplier of the safety data sheet

Supplier TEAL & MACKRILL LIMITED
LOCKWOOD STREET
HULL
HU2 0HN

+44(0)1482 320194(T)

+44(0)1482 219266(F)

info@teamac.co.uk

Contact person Technical Department -, 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri, as above

1.4. Emergency telephone number

Emergency telephone +44 (0) 1482 320194 Teamac (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)

SDS No. 11493

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 3 - H226

Health hazards Acute Tox. 4 - H312 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335 STOT RE 2 - H373

Environmental hazards Aquatic Chronic 3 - H412

2.2. Label elements

Pictogram



Signal word

Warning

413/G750 - RAPIDRY GLOSS - BLACK

| | |
|---|---|
| Hazard statements | <p>EUH208 Contains NEODECANOATE ACID, COBALT SALT. May produce an allergic reaction.</p> <p>H226 Flammable liquid and vapour.</p> <p>H312 Harmful in contact with skin.</p> <p>H315 Causes skin irritation.</p> <p>H319 Causes serious eye irritation.</p> <p>H335 May cause respiratory irritation.</p> <p>H373 May cause damage to organs through prolonged or repeated exposure.</p> <p>H412 Harmful to aquatic life with long lasting effects.</p> |
| Precautionary statements | <p>P101 If medical advice is needed, have product container or label at hand.</p> <p>P102 Keep out of reach of children.</p> <p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P260 Do not breathe vapour/ spray.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p> |
| Supplemental label information | EUH066 Repeated exposure may cause skin dryness or cracking. |
| Contains | Xylene Isomer Mixture |
| Supplementary precautionary statements | <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.</p> <p>P403+P235 Store in a well-ventilated place. Keep cool.</p> |

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

| | | |
|------------------------------|--|--|
| Xylene Isomer Mixture | | 30-60% |
| CAS number: 1330-20-7 | EC number: 215-535-7 | REACH registration number: 01-2119488216-32-0000 |
| Classification | Classification (67/548/EEC or 1999/45/EC) | |
| Flam. Liq. 3 - H226 | R10 Xn;R20/21 Xi;R38 | |
| Acute Tox. 4 - H312 | | |
| Acute Tox. 4 - H332 | | |
| Skin Irrit. 2 - H315 | | |
| Eye Irrit. 2 - H319 | | |
| STOT SE 3 - H335 | | |
| STOT RE 2 - H373 | | |
| Asp. Tox. 1 - H304 | | |
| Aquatic Chronic 3 - H412 | | |

413/G750 - RAPIDRY GLOSS - BLACK

| | | |
|--|--|--|
| HYDROCARBONS, C9-C11, <2% AROMATICS <1% | | |
| CAS number: — | EC number: 919-857-5 | REACH registration number: 01-2119463258-33-XXXX |
| Classification Flam. Liq. 3 - H226 STOT SE 3 - H336 Asp. Tox. 1 - H304 | Classification (67/548/EEC or 1999/45/EC) Xn;R65. R10,R66,R67. | |
| Carbon Black <1% | | |
| CAS number: 1333-86-4 | EC number: 215-609-9 | REACH registration number: 01-2119384822-32 |
| Classification Not Classified | Classification (67/548/EEC or 1999/45/EC) - | |
| HYDROCARBONS, C9, AROMATICS <1% | | |
| CAS number: — | EC number: 918-668-5 | REACH registration number: 01-2119455851-35-xxxx |
| Classification Flam. Liq. 3 - H226 STOT SE 3 - H335, H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411 | Classification (67/548/EEC or 1999/45/EC) Xn;R65. Xi;R37. N;R51/53. R10,R66,R67. | |
| Hydrocarbons, C10-13, n-alkanes, isoalkanes, cyclics, <2% aromatics <1% | | |
| CAS number: 64742-48-9 | EC number: 918-481-9 | REACH registration number: 01-2119457273-39-0000 |
| Classification Flam. Liq. 3 - H226 STOT SE 3 - H336 Asp. Tox. 1 - H304 | | |
| NEODECANOATE ACID, COBALT SALT <1% | | |
| CAS number: 27253-31-2 | EC number: 248-373-0 | |
| Classification Acute Tox. 4 - H302 Skin Sens. 1 - H317 Repr. 2 - H361f Aquatic Chronic 3 - H412 | Classification (67/548/EEC or 1999/45/EC) Xn;R22. Repr. Cat. 3;R62. N;R51/53. R43. | |

413/G750 - RAPIDRY GLOSS - BLACK

| | | |
|--|---|--|
| ZIRCONIUM SALT, 2-ETHYLHEXANOIC ACID <1% | | |
| CAS number: 22464-99-9 | EC number: 245-018-1 | REACH registration number: 01-2119979088-21-0002 |
| Classification Repr. 2 - H361d | Classification (67/548/EEC or 1999/45/EC) Repr. Cat. 3;R63. | |

| | | |
|--|--|---|
| 2-BUTANONE OXIME <1% | | |
| CAS number: 96-29-7 | EC number: 202-496-6 | REACH registration number: 01-2119539477-28 |
| Classification Acute Tox. 4 - H312 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Carc. 2 - H351 | Classification (67/548/EEC or 1999/45/EC) Carc. Cat. 3;R40 Xn;R21 R43 Xi;R41 | |

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|-----------------------------------|---|
| General information | Get medical attention immediately. Show this Safety Data Sheet to the medical personnel. |
| Inhalation | Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place. |
| Ingestion | Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. |
| Skin contact | Rinse with water. |
| Eye contact | Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes. |
| Protection of first aiders | First aid personnel should wear appropriate protective equipment during any rescue. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|----------------------------|--|
| General information | See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure. |
| Inhalation | A single exposure may cause the following adverse effects: Dryness of mouth and throat. Coughing, chest tightness, feeling of chest pressure. Overexposure to organic solvents may depress the central nervous system, causing dizziness and intoxication and, at very high concentrations, unconsciousness and death. Congestion of the lungs may occur, producing severe shortness of breath. During application and drying, solvent vapours will be emitted. Vapours in high concentrations are narcotic. |

413/G750 - RAPIDRY GLOSS - BLACK

| | |
|---------------------|--|
| Ingestion | A single exposure may cause the following adverse effects: Irritation. Nausea, vomiting. Symptoms following overexposure may include the following: Unconsciousness. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation. |
| Skin contact | A single exposure may cause the following adverse effects: Redness. Irritation. Discoloration of the skin. |
| Eye contact | A single exposure may cause the following adverse effects: Redness. Irritation. |

4.3. Indication of any immediate medical attention and special treatment needed

| | |
|-----------------------------|------------------------|
| Notes for the doctor | Treat symptomatically. |
|-----------------------------|------------------------|

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. Contains Hydrocarbons. The product is immiscible with water and will spread on the water surface.

Hazardous combustion products Hydrocarbons. Carbon monoxide (CO). Carbon dioxide (CO₂).

5.3. Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material. Provide adequate ventilation.

6.2. Environmental precautions

Environmental precautions Immiscible with water. Aquatic toxicity is unlikely to occur. However, large or frequent spills may have hazardous effects on the environment. Absorb spillage with non-combustible, absorbent material.

6.3. Methods and material for containment and cleaning up

413/G750 - RAPIDRY GLOSS - BLACK

Methods for cleaning up

Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Small Spillages: Collect spillage. Large Spillages: Absorb spillage with non-combustible, absorbent material. The contaminated absorbent may pose the same hazard as the spilled material. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Avoid the formation of mists. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment.

Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Store away from incompatible materials (see Section 10). Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Bund storage facilities to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not absorbent.

Storage class

Unspecified storage.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

Usage description

Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Xylene Isomer Mixture

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m³

Sk

Carbon Black

Long-term exposure limit (8-hour TWA): WEL 3,5 mg/m³

Short-term exposure limit (15-minute): WEL 7 mg/m³

HYDROCARBONS, C9, AROMATICS

Long-term exposure limit (8-hour TWA): WEL 19 ppm 100 mg/m³ vapour

413/G750 - RAPIDRY GLOSS - BLACK

NEODECANOATE ACID, COBALT SALT

Long-term exposure limit (8-hour TWA): WEL 0.1 mg/m³

ZIRCONIUM SALT, 2-ETHYLHEXANOIC ACID

Long-term exposure limit (8-hour TWA): WEL 5 mg/m³

Short-term exposure limit (15-minute): WEL 10 mg/m³

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

Xylene Isomer Mixture (CAS: 1330-20-7)

| | |
|-------------|---|
| DNEL | <p>Consumer - Inhalation; Long term systemic effects: 65.3 mg/m³</p> <p>Consumer - Dermal; Long term systemic effects: 1872 mg/kg/day</p> <p>Consumer - Oral; Long term systemic effects: 12.5 mg/kg/day</p> <p>Industry - Inhalation; Long term systemic effects: 221 mg/m³</p> <p>Industry - Inhalation; Short term : 442 mg/m³</p> <p>Consumer - Inhalation; Short term : 260 mg/m³</p> <p>Industry - Dermal; Long term systemic effects: 3182 mg/kg/day</p> |
| PNEC | <p>- Fresh water; 0.327 mg/l</p> <p>- marine water; 0.327 mg/l</p> <p>- Intermittent release; 0.327 mg/l</p> <p>- STP; 6.58 mg/l</p> <p>- Sediment (Freshwater); 12.46 mg/kg</p> <p>- Sediment (Marinewater); 12.46 mg/kg</p> <p>- Soil; 2.31 mg/kg</p> |

HYDROCARBONS, C9-C11, <2% AROMATICS

| | |
|-------------|--|
| DNEL | <p>Consumer - Oral; Long term systemic effects: 300 mg/kg/day</p> <p>Industry - Inhalation; Long term systemic effects: 1500 mg/m³</p> <p>Industry - Dermal; Long term systemic effects: 300 mg/kg/day</p> <p>Consumer - Dermal; Long term systemic effects: 300 mg/kg/day</p> <p>Consumer - Inhalation; Long term systemic effects: 900 mg/m³</p> |
| PNEC | <p>No PNEC available. Substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for the risk assessment of this complex substance.</p> |

Carbon Black (CAS: 1333-86-4)

| | |
|-------------|--|
| DNEL | <p>Consumer - Inhalation; Long term systemic effects: 2 mg/m³</p> |
| PNEC | <p>- Fresh water; 5 mg/l</p> <p>- marine water; 5 mg/l</p> |

HYDROCARBONS, C9, AROMATICS

| | |
|-------------|---|
| DNEL | <p>Consumer - Oral; Long term systemic effects: 11 mg/kg/day</p> <p>Consumer - Dermal; Long term systemic effects: 11 mg/kg/day</p> <p>Consumer - Inhalation; Long term systemic effects: 32 mg/m³</p> <p>Industry - Dermal; Long term systemic effects: 25 mg/kg/day</p> <p>Industry - Inhalation; Long term systemic effects: 150 mg/m³</p> |
|-------------|---|

413/G750 - RAPIDRY GLOSS - BLACK

PNEC No PNEC available. Substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for the risk assessment of this complex substance.

Hydrocarbons, C10-13, n-alkanes, isoalkanes, cyclics, <2% aromatics (CAS: 64742-48-9)

DNEL Workers - Inhalation; Long term systemic effects: 1500 mg/m³
 Workers - Dermal; Long term systemic effects: 300 mg/kg/day
 General population - Inhalation; Long term systemic effects: 900 mg/m³
 General population - Dermal; Long term systemic effects: 300 mg/kg/day
 General population - Oral; Long term systemic effects: 300 mg/kg/day

NEODECANOATE ACID, COBALT SALT (CAS: 27253-31-2)

DNEL Workers - Inhalation; Long term local effects: 0.2732 mg/m³
 General population - Inhalation; Long term local effects: 0.043 mg/m³
 General population - Oral; Long term systemic effects: 0.0649 mg/kg/day

PNEC - Fresh water; 0.003 Co mg/l
 - marine water; 0.00236 Co mg/l
 - STP; 0.37 Co mg/l
 - Sediment (Freshwater); 9.5 Co mg/kg/day
 - Sediment (Marinewater); 9.5 Cp mg/kg/day
 - Soil; 10.9 Co mg/kg/day

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimise worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimise exposure.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with European Standard EN166. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection

To protect hands from chemicals, gloves should comply with European Standards EN388 and 374. As a general principle, exposure should be managed by means other than the provision of protective gloves. Manufacturer's performance data suggest that the optimum glove for use should be: Wear protective gloves made of the following material: Polyvinyl alcohol (PVA). Thickness: 0.2 - 0.3 mm Permeation breakthrough time according to EN374 - class: (1-6) e.g. minimum 480 mins. Caution: The performance of gloves under actual working conditions can be significantly affected by many factors and the information provided according to EN374 may not accord with what is achieved in practice. We recommend that expert professional advice is sought that takes into account of the work processes and working environment applicable for each task where gloves are to be worn.

413/G750 - RAPIDRY GLOSS - BLACK

| | |
|--|---|
| Other skin and body protection | Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible. |
| Hygiene measures | Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Preventive industrial medical examinations should be carried out. Warn cleaning personnel of any hazardous properties of the product. |
| Respiratory protection | Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with European Standard EN14387. Full face mask respirators with replaceable filter cartridges should comply with European Standard EN136. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140. |
| Environmental exposure controls | Keep container tightly sealed when not in use. |

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|-----------------------------------|
| Appearance | Viscous liquid. Coloured liquid. |
| Colour | Black. |
| Odour | Characteristic. Organic solvents. |
| Odour threshold | Not determined. |
| pH | Technically not feasible. |
| Melting point | Not determined. |
| Initial boiling point and range | Not determined. |
| Flash point | 27 approx. °C Closed cup. |
| Evaporation rate | Not determined. |
| Evaporation factor | Not determined. |
| Upper/lower flammability or explosive limits | : 0.8 |
| Other flammability | Not determined. |
| Vapour pressure | Not determined. |
| Vapour density | heavier than air |
| Relative density | 1.00 @ @ 20°C |
| Solubility(ies) | Immiscible with water |
| Partition coefficient | Not determined. |
| Auto-ignition temperature | Not determined. |
| Decomposition Temperature | Not determined. |
| Viscosity | 2.0 - 2.2 (Cone & Plate) P @ 25°C |

413/G750 - RAPIDRY GLOSS - BLACK

| | |
|---|---------------------------------|
| Explosive properties | Not determined. |
| Explosive under the influence of a flame | Not considered to be explosive. |
| Oxidising properties | Not determined. |

9.2. Other information

| | |
|----------------------------------|---|
| Volatile organic compound | This product contains a maximum VOC content of 483 g/litre. |
|----------------------------------|---|

SECTION 10: Stability and reactivity

10.1. Reactivity

| | |
|-------------------|--|
| Reactivity | See the other subsections of this section for further details. |
|-------------------|--|

10.2. Chemical stability

| | |
|------------------|---|
| Stability | Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions. |
|------------------|---|

10.3. Possibility of hazardous reactions

| | |
|---|---|
| Possibility of hazardous reactions | No potentially hazardous reactions known. |
|---|---|

10.4. Conditions to avoid

| | |
|----------------------------|--|
| Conditions to avoid | Avoid heat. Containers can burst violently or explode when heated, due to excessive pressure build-up. |
|----------------------------|--|

10.5. Incompatible materials

| | |
|---------------------------|--------------------------------------|
| Materials to avoid | Oxidising agents. Acids - oxidising. |
|---------------------------|--------------------------------------|

10.6. Hazardous decomposition products

| | |
|---|--|
| Hazardous decomposition products | Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours. |
|---|--|

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - dermal

| | |
|---------------------------|----------|
| ATE dermal (mg/kg) | 1,432.11 |
|---------------------------|----------|

Acute toxicity - inhalation

| | |
|--------------------------------------|------|
| ATE inhalation (vapours mg/l) | 24.4 |
|--------------------------------------|------|

| | |
|----------------------------|---|
| General information | The severity of the symptoms described will vary dependent on the concentration and the length of exposure. |
|----------------------------|---|

| | |
|-------------------|--|
| Inhalation | A single exposure may cause the following adverse effects: Dryness of mouth and throat. Coughing, chest tightness, feeling of chest pressure. Overexposure to organic solvents may depress the central nervous system, causing dizziness and intoxication and, at very high concentrations, unconsciousness and death. Congestion of the lungs may occur, producing severe shortness of breath. During application and drying, solvent vapours will be emitted. Vapours in high concentrations are narcotic. |
|-------------------|--|

| | |
|------------------|--|
| Ingestion | A single exposure may cause the following adverse effects: Irritation. Nausea, vomiting. Symptoms following overexposure may include the following: Unconsciousness. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation. |
|------------------|--|

413/G750 - RAPIDRY GLOSS - BLACK

| | |
|---|--|
| Skin contact | A single exposure may cause the following adverse effects: Redness. Irritation. Discoloration of the skin. |
| Eye contact | A single exposure may cause the following adverse effects: Redness. Irritation. |
| Acute and chronic health hazards | This product has low toxicity. Only large quantities are likely to have adverse effects on human health. |
| Route of exposure | Ingestion Inhalation Skin and/or eye contact |
| Target organs | No specific target organs known. |
| Medical considerations | Skin disorders and allergies. Avoid vomiting and stomach flushing because of the risk of aspiration. |

Toxicological information on ingredients.

HYDROCARBONS, C9-C11, <2% AROMATICS

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,100.0

Species Rat

ATE oral (mg/kg) 5,100.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 5,100.0

Species Rabbit

ATE dermal (mg/kg) 5,100.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 5,100.0

Species Rat

ATE inhalation (vapours mg/l) 5,100.0

Skin corrosion/irritation

Skin corrosion/irritation Not irritating.

Serious eye damage/irritation

Serious eye damage/irritation Not irritating.

Respiratory sensitisation

Respiratory sensitisation Not sensitising.

Skin sensitisation

Skin sensitisation Not sensitising.

Germ cell mutagenicity

Genotoxicity - in vitro Chromosome aberration: Negative. This substance has no evidence of mutagenic properties.

413/G750 - RAPIDRY GLOSS - BLACK**Carcinogenicity**

Carcinogenicity Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity - fertility Fertility: - , Inhalation, Rat This substance has no evidence of toxicity to reproduction.

Reproductive toxicity - development Developmental toxicity: - : , Inhalation, Rat This substance has no evidence of toxicity to reproduction.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not available.

Aspiration hazard

Aspiration hazard Kinematic viscosity <= 20.5 mm²/s.

Inhalation

Vapours may cause drowsiness and dizziness. Central nervous system depression.

Ingestion

Harmful: danger of serious damage to health by prolonged exposure if swallowed.

Skin contact

Product has a defatting effect on skin. May cause allergic contact eczema.

Eye contact

No specific health hazards known.

Route of exposure

Inhalation Dermal

HYDROCARBONS, C9, AROMATICS**Acute toxicity - oral**

Acute toxicity oral (LD₅₀ mg/kg) 3,492.0

Species Rat

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

ATE oral (mg/kg) 3,492.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 3,160.0

Species Rabbit

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

ATE dermal (mg/kg) 3,160.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 6,193.0

Species Rat

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

ATE inhalation (vapours mg/l) 6,193.0

413/G750 - RAPIDRY GLOSS - BLACK

Skin corrosion/irritation

Animal data Repeated exposure may cause skin dryness or cracking.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicity None of the ingredients are listed or exempt.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity - development Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure STOT SE 3 - H335, H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Target organs Respiratory system, lungs Central nervous system

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Asp. Tox. 1 - H304 May be fatal if swallowed and enters airways. Pneumonia may be the result if vomited material containing solvents reaches the lungs.

General information

The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation

A single exposure may cause the following adverse effects: Irritation of nose, throat and airway. Difficulty in breathing. Coughing. Vapours may cause headache, fatigue, dizziness and nausea. Central nervous system depression. During application and drying, solvent vapours will be emitted. Vapours in high concentrations are narcotic.

Ingestion

Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation. Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

Skin contact

Repeated exposure may cause skin dryness or cracking. Discoloration of the skin.

413/G750 - RAPIDRY GLOSS - BLACK

| | |
|--------------------------|--|
| Eye contact | May cause temporary eye irritation. |
| Route of exposure | Ingestion Inhalation Skin and/or eye contact |
| Target organs | Central nervous system Respiratory system, lungs |

2-BUTANONE OXIME

| | |
|--|--|
| Other health effects | Carcinogen Category 2. |
| <u>Acute toxicity - oral</u> | |
| Acute toxicity oral (LD₅₀ mg/kg) | 2,528.0 |
| Species | Rat |
| ATE oral (mg/kg) | 2,528.0 |
| <u>Acute toxicity - dermal</u> | |
| ATE dermal (mg/kg) | 1,100.0 |
| General information | Known or suspected carcinogen for humans. |
| Skin contact | May cause sensitisation by skin contact. Harmful in contact with skin. |

SECTION 12: Ecological information

Ecotoxicity The product contains substances which are toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

12.1. Toxicity

Toxicity Based on available data the classification criteria are not met.

Ecological information on ingredients.**HYDROCARBONS, C9-C11, <2% AROMATICS****Acute aquatic toxicity**

| | |
|---|--|
| Acute toxicity - fish | LC50, > 96 hours: 1000 mg/l, Oncorhynchus mykiss (Rainbow trout) Substance did not cause acute toxicity to fish |
| Acute toxicity - aquatic invertebrates | Substance did not cause acute toxicity to the freshwater invertebrates EC ₅₀ , 48 hours: >1000 mg/l, Daphnia magna |
| Acute toxicity - aquatic plants | EC ₅₀ , > 72 hours: 1000 mg/l, Freshwater algae Substance did not cause acute toxicity to the freshwater green algae |
| Acute toxicity - microorganisms | EC ₅₀ , >: 100 mg/l, Activated sludge |

Chronic aquatic toxicity

| | |
|---|--|
| Chronic toxicity - fish early life stage | NOEC, 28 days: 0.131 mg/l, Oncorhynchus mykiss (Rainbow trout) |
| Chronic toxicity - aquatic invertebrates | NOEC, 28 days: 0.23 mg/l, Daphnia magna |

HYDROCARBONS, C9, AROMATICS

413/G750 - RAPIDRY GLOSS - BLACK

| | |
|---|--|
| Toxicity | Aquatic Chronic 2 - H411 Toxic to aquatic life with long lasting effects. |
| <u>Acute aquatic toxicity</u> | |
| Acute toxicity - fish | LC ₅₀ , 96 hours: 9.2 mg/l, Oncorhynchus mykiss (Rainbow trout) |
| Acute toxicity - aquatic invertebrates | EC ₅₀ , 48 hours: 3.2 mg/l, Daphnia magna |
| Acute toxicity - microorganisms | EC ₅₀ , 48 hours: 2.9 mg/l, |

12.2. Persistence and degradability

Persistence and degradability The degradability of the product is not known.

Ecological information on ingredients.

HYDROCARBONS, C9-C11, <2% AROMATICS

| | |
|--------------------------------------|---|
| Persistence and degradability | The product is readily biodegradable. |
| Phototransformation | Oxidises rapidly by photo-chemical reactions in air |
| Biodegradation | - 80 Degradation (%): 28 days Test - 301F Ready Biodegradability - Manometric Respiratory Test |

HYDROCARBONS, C9, AROMATICS

| | |
|--------------------------------------|--|
| Persistence and degradability | The degradability of the product is not known. |
| Biodegradation | - 78%: 28 days |

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

Ecological information on ingredients.

HYDROCARBONS, C9-C11, <2% AROMATICS

| | |
|----------------------------------|--|
| Bioaccumulative potential | The product contains potentially bioaccumulating substances. |
| Partition coefficient | log Pow: 5 - 6.7 |

HYDROCARBONS, C9, AROMATICS

| | |
|----------------------------------|---------------------------------------|
| Bioaccumulative potential | No data available on bioaccumulation. |
| Partition coefficient | Not available. |

12.4. Mobility in soil

Mobility The product is insoluble in water. Volatile liquid. The product contains organic solvents which will evaporate easily from all surfaces.

Ecological information on ingredients.

HYDROCARBONS, C9-C11, <2% AROMATICS

413/G750 - RAPIDRY GLOSS - BLACK

| | |
|--|---|
| Mobility | The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces. Readily absorbed into soil. |
| Adsorption/desorption coefficient | Not available. |
| Surface tension | 24.5 mN/m @ 20°C |

HYDROCARBONS, C9, AROMATICS

| | |
|-----------------|--------------------|
| Mobility | No data available. |
|-----------------|--------------------|

12.5. Results of PBT and vPvB assessment

| | |
|---|---|
| Results of PBT and vPvB assessment | This product does not contain any substances classified as PBT or vPvB. |
|---|---|

Ecological information on ingredients.

HYDROCARBONS, C9-C11, <2% AROMATICS

| | |
|---|---|
| Results of PBT and vPvB assessment | This substance is not classified as PBT or vPvB according to current EU criteria. |
|---|---|

HYDROCARBONS, C9, AROMATICS

| | |
|---|---|
| Results of PBT and vPvB assessment | This substance is not classified as PBT or vPvB according to current EU criteria. |
|---|---|

12.6. Other adverse effects

| | |
|------------------------------|-------------|
| Other adverse effects | None known. |
|------------------------------|-------------|

Ecological information on ingredients.

HYDROCARBONS, C9-C11, <2% AROMATICS

| | |
|------------------------------|------------|
| Other adverse effects | Not known. |
|------------------------------|------------|

HYDROCARBONS, C9, AROMATICS

| | |
|------------------------------|-------------|
| Other adverse effects | None known. |
|------------------------------|-------------|

SECTION 13: Disposal considerations

13.1. Waste treatment methods

| | |
|----------------------------|--|
| General information | The generation of waste should be minimised or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous. |
|----------------------------|--|

| | |
|-------------------------|--|
| Disposal methods | Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Waste packaging should be collected for reuse or recycling. Incineration or landfill should only be considered when recycling is not feasible. |
|-------------------------|--|

413/G750 - RAPIDRY GLOSS - BLACK

Waste class When this coating, in its liquid state, as supplied, becomes a waste, it is categorised as hazardous waste, with code 08 01 11* (SOLVENT BASED LIQUID WASTE). Part-used containers, not drained and/or rigorously scraped out and containing dried residues of the supplied coating, are categorised as hazardous waste, with code 08 01 11* (SOLVENT BASED LIQUID WASTE). If mixed with other wastes, the above waste code may not be applicable. Used containers, drained and/or rigorously scraped out and containing dry residues of the supplied coating, are categorised as non-hazardous waste, with code 15 01 02 (plastic packaging) or 15 01 04 (metal packaging).

SECTION 14: Transport information

General For limited quantity packaging/limited load information, consult the relevant modal documentation using the data shown in this section.

14.1. UN number

| | |
|------------------|------|
| UN No. (ADR/RID) | 1263 |
| UN No. (IMDG) | 1263 |
| UN No. (ICAO) | 1263 |

14.2. UN proper shipping name

| | |
|---------------------------------------|---|
| Proper shipping name (ADR/RID) | PAINT, contains Xylene Isomer Mixture, Class 3, PGIII, (28 °C) and Hydrocarbons, C9, Aromatics (MARINE POLLUTANT) |
| Proper shipping name (IMDG) | PAINT, contains Xylene Isomer Mixture, Class 3, PGIII, (28 °C) and Hydrocarbons, C9, Aromatics (MARINE POLLUTANT) |
| Proper shipping name (ICAO) | PAINT, contains Xylene Isomer Mixture, Class 3, PGIII, (28 °C) and Hydrocarbons, C9, Aromatics (MARINE POLLUTANT) |

14.3. Transport hazard class(es)

| | |
|---------------------|---|
| ADR/RID class | 3 |
| IMDG class | 3 |
| ICAO class/division | 3 |

Transport labels



14.4. Packing group

| | |
|-----------------------|-----|
| ADR/RID packing group | III |
| IMDG packing group | III |
| ICAO packing group | III |

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

413/G750 - RAPIDRY GLOSS - BLACK

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

EmS F-E, S-E

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Control of Substances Hazardous to Health Regulations 2002 (as amended).

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Commission Regulation (EU) No 2015/830 of 28 May 2015.
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

Inventories

EU - EINECS/ELINCS

None of the ingredients are listed or exempt.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.
RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.
IATA: International Air Transport Association.
ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.
IMDG: International Maritime Dangerous Goods.
CAS: Chemical Abstracts Service.
ATE: Acute Toxicity Estimate.
LC₅₀: Lethal Concentration to 50 % of a test population.
LD₅₀: Lethal Dose to 50% of a test population (Median Lethal Dose).
EC₅₀: 50% of maximal Effective Concentration.
PBT: Persistent, Bioaccumulative and Toxic substance.
vPvB: Very Persistent and Very Bioaccumulative.

Training advice Read and follow manufacturer's recommendations.

Revision comments Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 2015/830 Revision to sections 2, 8, 11 & 12 for reclassification of solvents.

Issued by Technical Dept. (P.E.)

413/G750 - RAPIDRY GLOSS - BLACK

| | |
|----------------------------------|---|
| Revision date | 28/09/2018 |
| Revision | 3.0 |
| Supersedes date | 11/05/2015 |
| SDS number | 11493 |
| SDS status | Approved. |
| Hazard statements in full | H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer. H361d Suspected of damaging the unborn child. H361f Suspected of damaging fertility. H373 May cause damage to organs through prolonged or repeated exposure. H373 May cause damage to organs (Respiratory system, lungs) through prolonged or repeated exposure if inhaled. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. EUH208 Contains NEODECANOATE ACID, COBALT SALT. May produce an allergic reaction. |
| Signature | Initials_____ |

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.